



▶ POE-TESTER+

Specifications

Interface	<ul style="list-style-type: none"> 1 x RJ45 TP connector PoE Power Input (PD)
LED indicators	<ul style="list-style-type: none"> IEEE 802.3at End-span/Pin 1236 (Amber) <ul style="list-style-type: none"> The PoE voltage is detected on pair 1,2,3,6 IEEE 802.3at Mid-span/Pin 4578 (Amber) <ul style="list-style-type: none"> The PoE voltage is detected on pair 4,5,7,8
Power input	60-/90-watt IEEE 802.3bt/at/af compliant with voltage
Temperature	-10° to 60°C (operating)
Humidity	5% to 95% (non-condensing)
Dimensions (DxWxH)	70.1 x 23 x 22 mm
Weight	20g
Cabling	UTP: Cat. 5 UTP cable or above, 100m (maximum)
Standard	<ul style="list-style-type: none"> IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus IEEE 802.3bt Power over Ethernet Plus Plus
Emission	CE Compliance



Power over Ethernet

▶ POE-TESTER+

IEEE 802.3bt/at/af Power over Ethernet Tester

- ▶ Easily tests RJ45 outlet for Power over Ethernet existence in a second
- ▶ Two LEDs indicate the types of PSE (Power Source Equipment)
 - End-span PoE Switch
 - Mid-span PoE Injector/Injector Hub
 - 4-pair 60-/90-watt PoE++ PoE Injector
- ▶ Compliant with IEEE 802.3bt/at/af standard
- ▶ Compact size, Plug and Play design

2010-AF0690-000

PLANET reserves the right to change specification without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright © 2020 PLANET Technology Corp. All rights reserved.

PLANET Technology Corporation

11F., No. 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan

www.planet.com.tw



Made in Taiwan

